

V Series Lever Lockset



Specifications

ANSI:	Meets & Exceeds ANSI A156.2, Series 4000, Grade 2
UL Listing:	UL Listed for "A" Label 3 Hour Fire Doors
Handing:	Non-Handed - Completely reversible
Clutching Mechanism:	Standard for Vandal Resistance
ADA:	Meets ADA and ANSI A117.1 accessibility codes
Latch Face:	1 1/8" x 2 1/4" face standard - Self adjusting front for square or beveled edge doors.
Backset:	2 3/4" standard, 2 3/8" available with 1" x 2 1/4" face
Latchbolt:	Stainless Steel with 1/2" projection
Lock Chassis:	Steel, Zinc dichromated for Corrosion Resistance
Door Preparation:	ANSI A115.2 - 2 1/8" crossbore
Door Thickness:	Factory set for 1 3/4" - Adjustable from 1 3/8" to 2"
Strike:	4 7/8" x 1 1/4" ASA standard - T & Full lip available
Cylinder:	6 Pin Solid Brass, C Keyway, 2 Silver Nickel Keys Cylinder plug face matches lock finish
Trim:	5" solid zinc diecast levers, 3" wrought brass roses
Lever Return:	Anti-sag mechanism with Independent lever return springs to prevent lever sag
Lever Designs:	Flat (standard, shown above) - Curved, Half Curve, S-A, S-B designs available by special order.
Standard Finishes:	US26D, US10B, US3 *PVD, US26 *PVD (*PVD = Lifetime Finish) Other finishes available by special order
Screws:	Combination screws for wood or metal doors & frames
Warranty:	Limited Lifetime Warranty



211 Endeavor Drive - PO Box 680
Rogersville, MO 65742
Ph 877-258-1262 Fx 877-888-0150

www.DesignHardware.net