

# Z Series Grade 1 Lever Lockset

---



## Specifications

---

<b>ANSI:</b>	Meets & Exceeds ANSI A156.2, Series 4000, Grade 1
<b>UL Listing:</b>	UL Listed for "A" Label 3 Hour Fire Doors
<b>Handing:</b>	Non-Handed - Completely reversible
<b>Clutching Mechanism:</b>	Standard for Vandal Resistance
<b>ADA:</b>	Meets ADA and ANSI A117.1 accessibility codes
<b>Latch Face:</b>	1 1/8" x 2 1/4" face standard - Self adjusting front for square or beveled edge doors.
<b>Backset:</b>	2 3/4" standard, 2 3/8" available with 1" x 2 1/4" face
<b>Latchbolt:</b>	Stainless Steel with 1/2" projection
<b>Lock Chassis:</b>	Steel, Zinc dichromated for Corrosion Resistance
<b>Door Preparation:</b>	ANSI A115.2 - Through bolted installation
<b>Door Thickness:</b>	Factory set for 1 3/4" - 1 3/8"(shims required) to 2"
<b>Strike:</b>	4 7/8" x 1 1/4" ASA standard - T & Full lip available
<b>Cylinder:</b>	6 Pin Solid Brass, C Keyway, 2 Silver Nickel Keys Cylinder plug face matches lock finish
<b>Trim:</b>	Solid zinc diecast levers, wrought brass roses
<b>Lever Designs:</b>	Flat (standard, shown above) - Curved
<b>Standard Finishes:</b>	US26D, US10B, US3 *PVD, US26 *PVD (*PVD = Lifetime Finish) Other finishes available by special order
<b>Screws:</b>	Combination screws for wood or metal doors & frames
<b>Cycle Testing:</b>	Tested to over 2 million cycles
<b>Warranty:</b>	Limited Lifetime Warranty



211 Endeavor Drive - PO Box 680  
Rogersville, MO 65742  
Ph 877-258-1262 Fx 877-888-0150

[www.DesignHardware.net](http://www.DesignHardware.net)